


MT4

350-380W

MS380M-60H

High Efficiency Full Black
Low LID Mono PERC with
MBB & Half-cut Technology



High transparency
solar glass

Features

High Efficiency up to 20.86%

Large area cells based on 166mm silicon wafers,
High module efficiency with high density interconnect technology

High Energy Yield

Excellent low irradiation performance,
Lower temperature coefficient and operating temperature

High Reliability

Resistant to harsh environments such as salt, ammonia, sand,
high temperature and high humidity areas


High Customer Value

Lowest guaranteed first year and annual degradation,
Compatible with existing mainstream system components

Quality Guarantee

12-Year Warranty for Materials and Processing

25-Year Warranty for Extra Linear Power Output



* Please refer to Mate Solar standard warranty for details

Certifications

IEC 61215, IEC 61730, UL 61730

ISO 9001: 2015: ISO Quality Management System

ISO 14001: 2015: ISO Environment Management System

ISO 45001: 2018: Occupational Health and Safety



WEB



WECHAT

Mechanical Data

Number of Cells	120 Cells (6x20)
Dimensions of Module L*W*H	1755 x 1038 x 35mm
Weight	19.5kg
Glass	Single glass 3.2mm coated tempered glass
Backsheet	Black
Frame	Black, anodized aluminium alloy
Junction Box	IP68 Rated, 3 Diodes
Cable	4.0mm ² , Portrait: 300mm / Landscape: 1200mm
Wind/Snow Load	2400Pa/5400Pa
Connector	MC Compatible

* Please check the installation manual for more details

Electrical Specification (STC*)

Maximum Power (Pmax/W)	350	355	360	365	370	375	380
Maximum Power Voltage (Vmp/V)	33.10	33.40	33.70	34.00	34.3	34.60	34.90
Maximum Power Current (Imp/A)	10.58	10.63	10.69	10.74	10.79	10.84	10.89
Open Circuit Voltage (Voc/V)	40.10	40.40	40.70	41.00	41.3	41.60	41.90
Short Circuit Current (Isc/A)	11.09	11.16	11.23	11.30	11.37	11.44	11.51
Module Efficiency (%)	19.22	19.49	19.77	20.04	20.32	20.59	20.86
Power Output Tolerance (W)	0~+5W						

* Irradiance 1000W/m², Cell Temperature 25°C, Air Mass 1.5

Electrical Specification (NMOT*)

Maximum Power (Pmax / W)	265	269	273	277	281	285	289
Maximum Power Voltage (Vmp / V)	31.30	31.60	31.9	32.20	32.50	32.80	33.10
Maximum Power Current (Imp / A)	8.47	8.52	8.56	8.61	8.65	8.69	8.74
Open Circuit Voltage (VOC / V)	37.90	38.20	38.5	38.80	39.10	39.40	39.70
Short Circuit Current (Isc / A)	8.93	8.99	9.05	9.11	9.17	9.23	9.29

* Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Maximum Ratings

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Max Series Fuse Rating	20A


Packaging Configuration

Module per Box	30 pieces
Module per 40' Container	780 pieces


Temperature Ratings

NMOT (Nominal Module Operating Temperature)	45±2°C
Temperature Coefficient of Isc	+0.048%/°C
Temperature Coefficient of Voc	-0.270%/°C
Temperature Coefficient of Pmax	-0.350%/°C


Module Dimension



Back View




A-A



B-B

I-V Curve at Different Temperature (380W)



I-V/P-V Curve at Different Temperature (380W)

